

Cork Rubber Sheet

Code: KXTS602



Description

Cork rubber sheet the compressibility of cork with the flexibility characteristics of rubber to make an excellent sealing material. All are available in rolls cut to your specifications for thickness and width.



Item no.: KXTS602

Cork Rubber Sheet

Item no.: KXTS602

* High resilience of rubber and compressibility of cork

* Excellent performance

Typical Application

* Make for gaskets of various engines of automobiles, tractors, plans, ships, and pipes petroleum, transformers, electric equipment, etc.

Technical Data

Item	Graded by hardness	
Hardness Shore A	55~70 (Medium)	70~85 (Hard)
Density g/cm ³	≤0.9(Medium)	≤1.05(Hard)
Tensile strength kg/cm ²	≥15(Medium)	≥20(Hard)
Compressibility (300psi load) %	15~30(Medium)	10~20(Hard)
Sealing pressure min	28 kg/cm ²	
Internal Pressure Max	3.5 kgf/cm ²	
Service Temperature Max	-40~120~150°C	

Dimensions

950x640mmx0.8~100mm (Untrimmed)

915x610mmx0.8~100mm (Trimmed)

Package: Carton Box

950x640x300mm

915x610x300mm

Roll:

1220mmxLengthx1~6mm

Other sizes on requirements.

Copyright © 2014-2015

Ningbo Kaxite Sealing Materials Co., Ltd.

No.134,Huancheng North Road,Jiangbei District,Ningbo City,Zhejiang Province,China (Zip:315020)

Website:<http://www.seal-china.com> E-mail:sales@seal-china.com,kaxite@seal-china.com